

## **LISTING OF CLAIMS**

This listing of claims replaces all prior versions and listings of claims in the patent application.

Claims 1-7 (cancelled)

Claim 8 (currently amended): An adjusting jig used for adjusting a button attaching apparatus which has: a first die capable of receiving one of a pair of button components and located on a predetermined advancement-retraction axis line; a second die capable of receiving the other of the pair of button components and located on the advancement-retraction axis line opposing the first die; a first side portion having a first holder supporting the first die in an attachable and detachable manner and in a manner movable along the advancement-retraction axis line; a second side portion having a second holder supporting the second die in an attachable and detachable manner; a drive mechanism provided at least one of the first side portion or the second side portion for moving the first holder or the second holder toward and away from each other along the predetermined advancement-retraction axis line; a first cushion provided on the first side portion for biasing the first die toward the second die; and a first cushion adjuster for adjusting the biasing force of the first cushion,

~~wherein the adjusting jig comprising a thickness adjuster for changing a position~~  
adjustment thickness (T0) ~~required for~~ used in adjusting relative position of the first holder and the second holder and a first adjustment thickness (T1) ~~required for~~ used in adjusting the biasing force of the first cushion ~~are selectable~~.

Claim 9 (currently amended): The adjusting jig of a button attaching apparatus according to claim 8, ~~further~~ the thickness adjuster comprising:

a base member having a shaft capable of being attached to the first holder or the second holder and a flange formed on an end of the shaft; and

an additional member formed in a ring capable of being inserted to the shaft and superposed on the flange,

wherein the position adjustment thickness ( $T_0$ ) and the first adjustment thickness ( $T_1$ ) can be formed only with the flange or the superposition of the flange and the additional member.

Claim 10 (currently amended): An adjusting jig used for adjusting a button attaching apparatus which has: a first die capable of receiving one of a pair of button components and located on a predetermined advancement-retraction axis line; a second die capable of receiving the other of the pair of button components and located on the advancement-retraction axis line opposing the first die; a first side portion having a first holder supporting the first die in an attachable and detachable manner and in a manner movable along the advancement-retraction axis line; a second side portion having a second holder supporting the second die in an attachable and detachable manner; a drive mechanism provided at least one of the first side portion or the second side portion for moving the first holder or the second holder toward and away from each other along the predetermined advancement-retraction axis line; a first cushion provided on the first side portion for biasing the first die toward the second die; a first cushion adjuster for adjusting the biasing force of the first cushion; a second cushion being stronger than the first cushion and being provided on the second side portion for biasing the second die toward the first die; and a second cushion adjuster for adjusting the biasing force of the second cushion,

~~wherein the adjusting jig comprising a thickness adjuster for changing a position adjustment thickness ( $T_0$ ) required for used in~~ adjusting relative position of the first holder and the second holder, a first adjustment thickness ( $T_1$ ) ~~required for used in~~ adjusting the biasing force of the first cushion, and a second adjustment thickness ( $T_2$ ) ~~required for used in~~ adjusting the biasing force of the second cushion ~~are selectable.~~

Claim 11 (currently amended): The adjusting jig of a button attaching apparatus according to claim 10, further the thickness adjuster comprising:

a base member having a shaft capable of being attached to the first holder or the second holder and a flange formed on an end of the shaft; and

an additional member formed in a ring capable of being inserted to the shaft and superposed on the flange,

wherein the position adjustment thickness (T0), the first adjustment thickness (T1) and the second adjustment thickness (T2) can be formed only with the flange or the superposition of the flange and the additional member.

Claim 12 (currently amended): The adjusting jig of a button attaching apparatus according to ~~claim 9~~ claim 11, further comprising a plurality of additional members,

wherein any of the additional members is abutted to the first holder or the second holder so that movement thereof is restricted in the direction of the advancement-retraction axis line in order to disable the biasing force of the first cushion or the second cushion, and

wherein the other of the additional members does not interfere with the first holder or the second holder for enabling the biasing force of the first cushion or the second cushion.